



Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1.(Currently Amended) A sled comprising

a hull having opposed first and second side walls;

a first strap anchor mounted on the first side wall;

a second strap anchor mounted on the second side wall;

the first and second strap anchors being disposed at longitudinal positions selected to be adjacent to a rider's thighs; and

a center strap anchor between the first and second strap anchors.

2.(Original) The sled of claim 1, further comprising a strap extending from the first strap anchor to the second strap anchor, the strap passing through the center strap anchor.

3.(Original) The sled of claim 1, further comprising a first strap extending from the first strap anchor to the center strap anchor and a second strap extending from the center strap anchor to the second strap anchor.

4.(Original) The sled of claim 1, wherein the center strap anchor comprises a bar supported by at least one leg extending from a floor of the hull.

5.(Original) The sled of claim 1, wherein the center strap anchor defines an aperture for receiving a strap.

6.(Original) The sled of claim 1, wherein the center strap anchor is integrally molded with the hull.

7.(Original) The sled of claim 1, wherein the center strap anchor is shaped to conform to a rider's thigh.

8. (Original) The sled of claim 1, wherein the center strap anchor is disposed midway between the first and second strap anchors.

9. (New) A sled comprising

a hull having opposed first and second side walls;

a first strap anchor mounted on the first side wall;

a second strap anchor mounted on the second side wall;

a center strap anchor between the first and second strap anchors;

a first strap extending from the first strap anchor to the center strap anchor; and

a second strap extending from the center strap anchor to the second strap anchor

10. (New) A sled comprising

a hull having opposed first and second side walls;

a first strap anchor mounted on the first side wall;

a second strap anchor mounted on the second side wall; and

a center strap anchor between the first and second strap anchors, the center strap anchor including a bar supported by at least one leg extending from a floor of the hull.